

LP6500: Double drum roller

3382 0000 01



[Create PDF sheet](#)

[Request information](#)

Construction and Mining
+971 (0) 4 886 1996
[Send an email](#)

Quick links

- ▶ [Atlas Copco Print Shop](#)
- ▶ [Atlas Copco Photo Archive](#)

[Product information](#)

Double drum rollers are suitable for compacting thin layers on granular soils and asphalt. They are mostly used for small jobs, repair work and compaction in confined areas.

Features & benefits

- ▶ Fully hydraulic
- ▶ Large, removable water tank
- ▶ Built-in oil cooler for increased lifetime of vital components
- ▶ Heavy-duty protection frame with single lifting point for easy transportation
- ▶ Minimum overhang and high curb clearance
- ▶ Powerful engine for reliable operations

Applications

- ▶ Silt
- ▶ Sand & Gravel
- ▶ Clay
- ▶ Asphalt

Technical data

Units: [Metric](#) [Imperial](#)

Technical Specifications	
Operating mass	1534 lb
Centrifugal force	-
Drum width	25 9/16 inch
Engine brand	Hatz
Power	6.8 kW
Speed, forward	-
Speed, reverse	-
Amplitude	0 inch
Frequency	61 Hz
Sound power level guaranteed*	107 dB(A)
Sound pressure level at operators ear	90 dB(A)
Vibration emission value*	4.3 m/s ²

